

TempDex 710

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile sandy
- **Length (inches)** 9.5-11
- **Thickness (inches)** Lt. Wt.
- **Wrist** Knitted wrist
- **Colour/Color** Yellow
- **Interior finish** Seamless textile support
- **Exterior finish** Dots
- **Size / EAN** 7 9 11
- **Packaging** 1 pair/bag - 10 pairs/bag - 50 pairs/carton
- **Complementary information** Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 2



Dexterity EN 420 : 5/5



X1XXXX

4111X

Legends

EN 388 MECHANICAL HAZARDS



PERFORMANCE LEVELS

0-4 0-5 0-4 0-4 A-F (P)

- Impact protection
- Cut resistance according to ISO 13997
- Puncture resistance
- Tear resistance
- Blade cut resistance
- Abrasion resistance

EN 407 THERMAL RISKS heat and fire



PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4

- Resistance to large quantities of molten metal
- Resistance to small drops of molten metal
- Radiant heat resistant
- Convective heat resistance
- Contact heat resistance
- Burning behaviour

CHEMICAL RISKS

EN ISO 374-1



U V W X Y Z

A Methanol
B Acetone
C Acetonitrile
D Dichloromethane
E Carbon Disulfide
F Toluene
G Diethylamine
H Tetrahydrofurane
I Ethyl acetate

EN ISO 374-1



X Y Z

J n-Heptane
K Sodium hydroxide 40%
L Sulphuric acid 96%
M Nitric acid 65%
N Acetic acid 99%
O Ammonia 25%
P Hydrogen peroxide 30%
S Hydrofluoric acid 40%
T Formaldehyde 37%

EN ISO 374-1



X Y Z

MICRO-ORGANISMS

EN ISO 374-5



Protection against bacteria, fungi

EN ISO 374-5



Protection against bacteria, fungi, virus

VIRUS



COLD HAZARDS

PERFORMANCE LEVELS

0-4 0-4 0 or 1

- Water permeability
- Contact cold resistance
- Convective cold resistance



RADIOACTIVE CONTAMINATION



CUT RESISTANCE

A1 ≥ 200 G A4 ≥ 1500 G A7 ≥ 4000 G
A2 ≥ 500 G A5 ≥ 2200 G A8 ≥ 5000 G
A3 ≥ 1000 G A6 ≥ 3000 G A9 ≥ 6000 G

For more details: www.mapa-pro.com

MAPA
PROFESSIONAL

www.mapa-pro.com

SPECIFIC ADVANTAGES

- Thin, anatomically-shaped glove ensures dexterity
- Excellent abrasion resistance: longer lasting
- Available in vending machine packaging

MAIN FIELDS OF USE

Ceramic and plastics industry

- Handling of composite materials after heat processing

Other industries

- Handling of moulds in the ceramic industry
- Handling of hot steel after welding
- Handling of hot piping

Construction Industry (Heating engineers/Plumbers)

- Maintaining pipes, heating equipment

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- It is not recommended for persons sensitized to dithiocarbamates and to natural latex (wrist with elastic natural rubber)
- Do not use in direct contact with a flame
- Put the gloves on dry, clean hands.
- Ensure the inside of the gloves is dry before putting them on again.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

- Store the glove in their original packaging protected from heat, light and humidity.

Laundering conditions

- Caution: improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

Food contact US

- FDA 21CFR 177.2600

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/12/18/3062
- **Issued by the notified body nr** : 0075 - C.T.C. – 4 rue Hermann Frenkel - F-69367 LYON CEDEX 07 FRANCE