Hylite® 47-402

TECHNICAL DATASHEET

Multi-purpose

Print date 08-04-2016

Glove material

- Nitrile (Coating material)
- Interlock cotton (Liner material)

Possible Harmful ingredients

Sensitizers

No sensitizers

Reach Regulation 1907/2006

For more information, please consult the REACH statement on the Ansell website

Properties

- Ergonomically designed for superior comfort
- Superior flexibility and finger dexterity
- Exceptional cut, puncture and abrasion resistance
- Outstanding dry grip

EN Test Data

Abrasion resistance:

Performance level 3

Blade cut resistance:

Performance level 1

Tear resistance:

Performance level 1

Puncture resistance:

Performance level 1

European conformity

Gloves conform to the requirements of the European Directive 89/686/EEC and to the European standards EN 420:2003 + A1:2009 and EN 388:2003

They are categorised in "Intermediate Design" (= Protection against intermediate risks).

EC-Type Examination Certificate for the final product by Centexbel

Technologiepark 7 B-9052 Zwijnaarde

Application - Limitations of use

Hand (mechanical) protection

Do not use against flames or temperatures &It; -25°C or > 140°C

Do not use against chemicals; the glove is not liquidproof Do not use for heavy duty mechanical applications

Storage

Keep away from sources of ozone or ignition. Keep out of direct sunlight; store in a cool and dry place.

| Construction | Liner Coating m | naterial Finishing | Cuff style | Colour | EN Size | Length mm | Packaging |
|--------------|------------------------------|--------------------|------------|--------|-------------|-----------|--|
| Cut & sewn | Interloc Nitrile k cotton | Fully coated | Knitwrist | Blue | 7, 8, 9, 10 | 270 | 12 pairs in a bag; 12 bags in a carton |

