

**Product Datasheet Safety Helmet airwing C  
with constant ventilation, helmet shell fully closed at front, permanently  
open at rear**



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth**

<p><b>Product characteristics</b></p>	<ul style="list-style-type: none"> <li>* size and weight optimised helmet</li> <li>* trendy design</li> <li>* Constant ventilation, helmet shell fully closed at front, permanently open at rear</li> <li>* optimal fit, high wearing comfort</li> <li>* 6-point textile suspension harness optionally with wheel ratchet system</li> <li>* approved and labeled for use in temperatures as low as <math>-30^{\circ}</math> C</li> <li>* side slots for attaching ear defenders or visors</li> <li>* suitable for head sizes of 51-61 cm resp. 52-61 cm (wheel ratchet system)</li> <li>* large printing areas</li> <li>* Optimal fit, high wearing comfort</li> </ul>
---------------------------------------	--

<b>Technical details</b>	
<b>Helmet shell</b>	
Material	PE
Weight	ca. 290 g
<b>Interior</b>	<ul style="list-style-type: none"> <li>* 6-point-textile suspension harness</li> <li>* Headband made of high quality PE</li> <li>* Circulating pad</li> <li>* Easy to replace sweatband</li> <li>* Medically shaped neck band to prevent slide on overhead working</li> </ul>
<b>Versions</b>	
<b>Conventional suspension harness</b>	
Weight	ca. 86 g
Colours / Art. No.	white 9761 020 yellow 9761 120 blue 9761 520
<b>Suspension harness with wheel ratchet system for infinite width adjustment</b>	
Weight	ca. 98 g
Colours / Art. No.	white 9761 030 yellow 9761 130 blue 9761 530
	25 pieces / box
<b>Packing</b>	
<b>Standards</b>	DIN EN 397 in combination with EG-guideline 89/686/EWG